

# CISCO SMART DEVICES



Cisco SPA504G

Cisco SPA514G

Cisco SPA525G2

	Cisco SPA504G	Cisco SPA514G	Cisco SPA525G2
<b>Description</b>	The Cisco SPA 504G 4-line IP Phone provides small businesses a rich user experience with a monochrome backlit display for ease of use, aesthetics, and on-screen applications; HD voice for unsurpassed voice clarity; enhanced full duplex speaker phone for clear conversations across the desk; and an integrated switch port to connect your computer.	The Cisco SPA514G 4-Line IP Phone with 2-Port Gigabit Ethernet Switch provides advanced voice and data communications features small businesses need to stay productive and responsive. With hundreds of features and configurable service parameters, the Cisco SPA514G addresses the requirements of traditional business users while building on the advantages of IP telephony.	The Cisco SPA525G2 IP phone can easily grow with your business. New features can be added to the phone over time via firmware updates. New employees or employees who need to move locations can simply plug in their preconfigured phones anywhere on the network, and the network will recognize the change. The phone also provides the option for wireless network connectivity, providing unrestricted placement.
<b>LCD Display</b>	128 x 64 pixel LCD display - monochrome backlit	128 x 64 pixel LCD display - monochrome backlit	320 x 240 pixel, QVGA display - color
<b>Color</b>			✓
<b>Touchscreen</b>			
<b>HD Voice</b>	✓		✓
<b>Intercom</b>	✓	✓	✓
<b>Video Calling</b>			
<b>Headset</b>	✓	✓	✓
<b>Line #s</b>	✓	4	5
<b>Personal Directory</b>	100 with auto dial	100 with auto dial	100 with auto dial
<b>Corporate Directory</b>	✓	✓	✓
<b>Call Park</b>	✓	✓	✓
<b>Busy Lamp Field (BLF)</b>			
<b>Power over Ethernet (PoE)</b>	✓	✓	✓
<b>WiFi</b>			✓
<b>USB</b>			✓
<b>Bluetooth</b>			✓
<b>Gigabit</b>		✓	✓
<b>TLS/SRTP/HTTPS</b>	✓	✓	✓

# CISCO SMART DEVICES



	Cisco 7940G	Cisco 7960G
<b>Description</b>	The Cisco Unified IP Phone 7940G is well suited for employees in a basic office cubicle environment--such as transaction type workers-- who conduct a moderate amount of business by phone.	The Cisco Unified IP Phone 7960G is designed to meet the communication needs of professional workers in enclosed office environments--employees who experience a high amount of phone traffic in the course of a business day. This IP phone supports access to multiple telephone lines (or a combination of lines and direct access to telephony features) and includes high-quality, hands-free speakerphone capability and built-in headset connectivity. A large pixel-based display provides supplemental information, access to applications, and makes it easy to use telephone features.
<b>LCD Display</b>	320 x 222 Grayscale Pixel Display	320 x 222 Grayscale Pixel Display
<b>Color</b>		
<b>Touchscreen</b>		
<b>HD Voice</b>		
<b>Intercom</b>	✓	✓
<b>Video Calling</b>		
<b>Headset</b>	✓	✓
<b>Line #s</b>	2	6
<b>Personal Directory</b>	✓	✓
<b>Corporate Directory</b>	✓	✓
<b>Call Park</b>	✓	✓
<b>Busy Lamp Field (BLF)</b>		
<b>Power over Ethernet (PoE)</b>	✓	✓
<b>WiFi</b>		
<b>USB</b>		
<b>Bluetooth</b>		
<b>Gigabit</b>		
<b>TLS/SRTP/HTTPS</b>	✓	✓

# CISCO SMART DEVICES



Cisco SPA500DS

<b>Description</b>	The Cisco ® SPA500DS 15-Button Attendant Console is part of the Cisco Small Business Series and designed for use with the Cisco SPA500 Series IP Phones. It is an ideal solution for small businesses wanting to simplify incoming call handling by quickly directing calls to the requested party and also to monitor line status from a central location.
<b>Ports</b>	2 auxiliary
<b>Buttons</b>	15
<b>Expandable Lines</b>	30
<b>Illuminated Line Status</b>	✓
<b>Call transfer</b>	✓
<b>Speed dial</b>	✓
<b>Direct Station Selection (DSS)</b>	
<b>Busy lamp field</b>	✓
<b>One-touch transfer</b>	✓
<b>Call pickup</b>	✓
<b>SPECIFICATIONS</b>	
<b>Multicolored LEDs</b>	
<b>Dimensions W x H x D</b>	4 x 8.5 x 1.5 in.
<b>Unit weight</b>	2 lb
<b>Power</b>	Provided by host Cisco SPA 500 Series IP phone
<b>Certification</b>	FCC, cUL, CE, Canadian Interference-Causing Equipment Standard ICES-003